



## Intel 3647 Series 240W 4U Server CPU Cooler

### SF6P4U-F003-A01



#### Features :

- Best-In-Class Thermal Performance: CPU Temperatures below 57°C @ 25°C Ambient**  
 Cooltron's Six Ø6mm Heat Pipes and Zipped Stamping Fin Stack with 92 x 25 mm PWM Fan accelerate up to 240W heat vortex dissipation, and patented Flat & Tight-fitting Heat Pipes embedding & engaging technologies enable to reduce the total thermal resistance to the minimum that help drop CPU temperatures instantly to avoid any overheated CPU breakdown
- PWM Fan for Smart Control & Power Saving; Low Noise for Quiet Operation**  
 PWM featured Fan can adjust fan speeds to different CPU thermal requirements and save power consumption. Low Noise feature also help create a quieter servers-intensive working place
- Comprehensive Intel CPU Compatibility**  
 Supports Square Type Intel LGA 3647 Sockets for compatible Intel CPUs – Xeon Phi X200, Xeon Phi 72x5, Skylake-SP, Cascade Lake – SP/AP, Cascade Lake – W
- Easy & Flexible Installation**  
 Cooltron's complete CPU Cooler package including mounting system and thermal paste ensures easy and quick installation. It's also flexible for user to install the CPU Cooler from any angles.

Intel Socket 3647 Series

#### CPU Temperature Rise

| Server Size | CPU Socket                  | TDP(W) | Ambient Temperature Ta (°C) | CPU Temperature Tc (°C) | Temperature Rise ΔT (°C) | Thermal Resistance (°C/W) |
|-------------|-----------------------------|--------|-----------------------------|-------------------------|--------------------------|---------------------------|
| 4U          | Intel FCLGA 3647 Square ILM | 240.00 | 25.00                       | 56.82                   | 31.82                    | 0.133                     |

#### Product Information:

|                        |  |                    |                 |            |
|------------------------|--|--------------------|-----------------|------------|
| Model Number:          | SF6P4U-F003-A01  | Fan                | Dimension (mm): | 90*90*25   |
| TDP (W):               | 240W   |                    | Air Flow (CFM): | 51.41(max) |
| Compatible CPU Socket: | Intel FCLGA 3647 Square ILM                                  |                    | Pres. (mm-H2O): | 3.41(max)  |
| Application:           | 4U Server and up (Active)                                    |                    | Noise (dBA):    | 32.4       |
| Dimension (mm):        | 105.7 x 95 x 126.3   |                    | Speed (RPM):    | 2,800 ±10% |
| Heat Sinks:            | AL Base + Cu Block + AL Fin + Heatpipe(Ø 6mm x 6) + 9225 Fan |                    | MTTF (hours):   | 50,000     |
|                        |  |                    | Voltage (VDC):  | 12         |
|                        |  |                    | Current (mA):   | 350        |
|                        |  | Power Connector:   | 4-pin PWM       |            |
|                        |  | Power Consumption: | 4.2 W           |            |

Applications: Data-Center, Rack & Tower Servers, High Speed Computing