

DC AXIAL FAN 40x40x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 15%-65%RH)
 Storage Temperature: -20°C~85°C(Humidity 15%-65%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 14.7 g Packing: 400PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD4010B05W3-88A ※	5	3.5~5.5	5.40	1.40	21.40	4,000	150	0.75	B,S	①
FD4010B05W5-88A ※	5	3.5~5.5	6.90	2.10	24.70	5,000	200	1.00	B,S	②
FD4010B05W7-88A ※	5	3.5~5.5	8.40	3.00	29.50	6,000	250	1.25	B,S	③
FD4010B05W9-88A ※	5	3.5~5.5	10.10	4.20	34.20	7,700	400	2.00	B,S	④
FD4010B12W3-88A	12	6.0~13.8	5.40	1.40	21.40	4,000	100	1.20	B,S	①
FD4010B12W5-88A	12	6.0~13.8	6.90	2.10	24.70	5,000	150	1.80	B,S	②
FD4010B12W7-88C	12	6.0~13.8	8.40	3.00	29.50	6,000	200	2.40	B,S	③
FD4010B12W7-88A	12	6.0~13.8	10.10	4.20	34.20	7,700	200	2.40	B,S	④

- For "Sleeve" bearing versions, change the "B" in the model number to "S" respectively.
- If model depicts "※", UL approvals can be implemented upon request.

Specifications are subject to change without notice

