

DC AXIAL FAN 50x50x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 20 g Packing: 400PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD5010B12W3-73	★▲ 12	9.6~13.2	4.80	1.10	19.50	3,400	160	1.92	B,L,S	①
FD5010B12W5-73	★▲ 12	9.6~13.2	5.90	1.60	23.50	4,200	250	3.00	B,L,S	②
FD5010B12W7-73	★▲ 12	9.6~13.2	7.20	2.10	26.40	5,000	350	4.20	B,L,S	③

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

