

DC AXIAL FAN 60x60x10mm

Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: $10M\Omega$, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: $-20^{\circ}C\sim 70^{\circ}C$ (Humidity 15%-90%RH)
 Storage Temperature: $-40^{\circ}C\sim 85^{\circ}C$ (Humidity 15%-90%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 28 g Packing: 300PCS/CTN



DC Axial Fans

Model Number		Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6010S05W7-61	★▲	5	3.5~5.75	18.80	3.20	35.50	4,200	350	1.75	S	①
FD6010S05W5-61	★▲	5	3.5~5.75	16.10	2.50	30.50	3,600	220	1.10	S	②
FD6010S05W3-61	★▲	5	3.5~5.75	12.30	1.40	26.60	3,000	170	0.85	S	③
FD6010B05W7-61	★▲	5	3.5~5.75	18.80	3.20	35.50	4,200	350	1.75	B	①
FD6010B05W5-61	★▲	5	3.5~5.75	16.10	2.50	30.50	3,600	220	1.10	B	②
FD6010B05W3-61	★▲	5	3.5~5.75	12.30	1.40	26.60	3,000	170	0.85	B	③
FD6010S12W7-61	★▲	12	6.0~13.8	18.80	3.20	35.50	4,200	220	2.64	S	①
FD6010S12W5-61	★▲	12	6.0~13.8	16.10	2.50	30.50	3,600	170	2.04	S	②
FD6010S12W3-61	★▲	12	6.0~13.8	12.30	1.40	26.60	3,000	140	1.68	S	③
FD6010B12W7-61	★▲	12	6.0~13.8	18.80	3.20	35.50	4,200	220	2.64	B	①
FD6010B12W5-61	★▲	12	6.0~13.8	16.10	2.50	30.50	3,600	170	2.04	B	②
FD6010B12W3-61	★▲	12	6.0~13.8	12.30	1.40	26.60	3,000	140	1.68	B	③
FD6010S24W7-61	★▲	24	12.0~27.6	18.80	3.20	35.50	4,200	110	2.64	S	①
FD6010S24W5-61	★▲	24	12.0~27.6	16.10	2.50	30.50	3,600	90	2.16	S	②
FD6010S24W3-61	★▲	24	12.0~27.6	12.30	1.40	26.60	3,000	70	1.68	S	③
FD6010B24W7-61	★▲	24	12.0~27.6	18.80	3.20	35.50	4,200	110	2.64	B	①
FD6010B24W5-61	★▲	24	12.0~27.6	16.10	2.50	30.50	3,600	90	2.16	B	②
FD6010B24W3-61	★▲	24	12.0~27.6	12.30	1.40	26.60	3,000	70	1.68	B	③

