

DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max, 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~70°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #26 AWG
 Weight: 60 g Packing: 200PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W3-73	★▲ 12	9.6~13.2	16.00	3.20	31.80	3,400	220	2.64	B,L,S	①
FD6025B12W5-73	★▲ 12	9.6~13.2	24.80	7.00	39.20	5,000	350	4.20	B,L,S	②
FD6025B12W7-73	★▲ 12	9.6~13.2	33.00	11.60	41.90	6,600	550	6.60	B,L,S	③

- For "Long Life", or "Sleeve" bearing versions, change the "B" in the model number to "L", or "S" respectively.
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

