

DC AXIAL FAN 70x70x10mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)
Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)
Lead Wire: UL Type #26 AWG
Weight: 35 g **Packing:** 300PCS/CTN



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD7010B05W3-83	5	4.0~5.75	18.40	1.40	24.10	2,600	160	0.80	B	①
FD7010B05W5-83	5	4.0~5.75	22.90	2.20	30.00	3,200	260	1.30	B	②
FD7010B05W7-83	5	4.0~5.75	26.20	2.80	33.00	3,600	340	1.70	B	③
FD7010B12W3-83	12	6.0~13.8	18.40	1.40	24.10	2,600	80	0.96	B	①
FD7010B12W5-83	12	6.0~13.8	22.90	2.20	30.00	3,200	120	1.44	B	②
FD7010B12W7-83	12	6.0~13.8	26.20	2.80	33.00	3,600	190	2.28	B	③

• For "Fluid Lubricant" bearing version, change the "B" in the model number to "F".

Specifications are subject to change without notice

