

DC AXIAL FAN 92x92x38mm

(High Performance Fan Series)



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 5%-90%RH)
 Storage Temperature: -40°C~80°C(Humidity 5%-95%RH)
 Lead Wire: UL Type #24 AWG
 Weight: 200 g Packing: 60PCS/CTN



- High Airflow
- Extremely High Static Pressure



DC Axial Fans

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD9238B12W3-87	★▲ 12	7.0~13.2	98.60	18.00	51.20	4,300	500	6.00	B	①
FD9238B12W5-87	★▲ 12	7.0~13.2	110.80	22.20	57.10	5,000	900	10.80	B	②
FD9238B12W7-87	★▲ 12	7.0~13.2	125.30	28.90	63.00	6,000	1,200	14.40	B	③
FD9238B12W9-87	★▲ 12	7.0~13.2	147.80	37.60	66.00	7,000	2,500	30.00	B	④
FD9238B12W11-87	★▲ 12	7.0~13.2	158.30	43.20	67.50	7,500	2,710	32.52	B	⑤
FD9238B24W3-87	★▲ 24	14.0~26.4	98.60	18.00	51.20	4,300	350	8.40	B	①
FD9238B24W5-87	★▲ 24	14.0~26.4	110.80	22.20	57.10	5,000	450	10.80	B	②
FD9238B24W7-87	★▲ 24	14.0~26.4	125.30	28.90	63.00	6,000	760	18.24	B	③
FD9238B24W9-87	★▲ 24	14.0~26.4	147.80	37.60	66.00	7,000	1,100	26.40	B	④
FD9238B24W11-87	★▲ 24	14.0~26.4	158.30	43.20	67.50	7,500	1,650	39.60	B	⑤
FD9238B48W3-87	★▲ 48	28.0~56.0	98.60	18.00	51.20	4,300	240	11.52	B	①
FD9238B48W5-87	★▲ 48	28.0~56.0	110.80	22.20	57.10	5,000	280	13.44	B	②
FD9238B48W7-87	★▲ 48	28.0~56.0	125.30	28.90	63.00	6,000	410	19.68	B	③
FD9238B48W9-87	★▲ 48	28.0~56.0	147.80	37.60	66.00	7,000	600	28.80	B	④
FD9238B48W11-87	★▲ 48	28.0~56.0	158.30	43.20	67.50	7,500	900	43.20	B	⑤

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

