

DC AXIAL FAN 120x120x38mm

(High Performance Fan Series)



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 15%-65%RH)
 Storage Temperature: -20°C~85°C(Humidity 15%-65%RH)
 Lead Wire: UL Type #24 AWG
 Weight: 292 g Packing: 40PCS/CTN

- High Airflow
- Extremely High Static Pressure

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD1238B12W3-88	★▲ 12	6.0~13.8	196.60	11.80	59.00	3,500	1,900	22.80	B	①
FD1238B12W5-88	★▲ 12	6.0~13.8	226.70	13.40	64.60	4,000	2,500	30.00	B	②
FD1238B12W7-88	★▲ 12	6.0~13.8	262.30	17.30	66.20	4,500	3,000	36.00	B	③
FD1238B24W3-88	★▲ 24	15.0~30.0	196.60	11.80	59.00	3,500	1,200	28.80	B	①
FD1238B24W5-88	★▲ 24	15.0~30.0	262.30	17.30	66.20	4,500	1,800	43.20	B	③
FD1238B24W7-88	★▲ 24	15.0~30.0	303.10	22.50	69.00	5,500	2,800	67.20	B	④
FD1238B48W3-88	★▲ 48	25.0~60.0	196.60	11.80	59.00	3,500	700	33.60	B	①
FD1238B48W5-88	★▲ 48	25.0~60.0	262.30	17.30	66.20	4,500	1,000	48.00	B	③
FD1238B48W7-88	★▲ 48	25.0~60.0	303.10	22.50	69.00	5,500	1,300	62.40	B	④

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

