

# DC BLOWER 60x60x25mm



Housing/Blade: Thermoplastic PBT, UL 94V-0  
 Insulation Resistance: 10M $\Omega$ , 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame  
 Operation Temperature: -20°C~70°C(Humidity 15%-90%RH)  
 Storage Temperature: -40°C~85°C(Humidity 15%-90%RH)  
 Lead Wire: UL Type #26 AWG  
 Weight: 52 g      Packing: 200PCS/CTN



DC Blowers

Model Number	Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FBD6025B12W3-81 ★	12	6.0~13.8	5.20	5.50	23.10	2,500	100	1.20	B	①
FBD6025B12W5-81 ★	12	6.0~13.8	7.40	11.60	34.00	3,500	220	2.64	B	②
FBD6025B12W7-81 ★	12	6.0~13.8	9.60	22.70	40.40	4,500	400	4.80	B	③
FBD6025B12W9-81 ★	12	6.0~13.8	11.80	34.20	46.30	5,500	450	5.40	B	④
FBD6025B24W3-81 ★	24	16.0~27.6	5.20	5.50	23.10	2,500	60	1.44	B	①
FBD6025B24W5-81 ★	24	16.0~27.6	7.40	11.60	34.00	3,500	120	2.88	B	②

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

