

AC AXIAL FAN 80x80x25mm



Housing: Die-Cast Aluminum, Painted Black
Blade: Thermoplastic PBT, UL 94V-0
Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minute
Operation Temperature: -10°C-70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C-85°C(Humidity 35%-85%RH)
Motor Protection: Impedance Protected
Weight: 250 g **Packing:** 60PCS/CTN



Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA8025B11T5-96	115	50/60	18.3/20.3	5.2/5.9	28.6/32.5	2,400/3,100	130/110	12/10	B,S	①/②
FA8025B11T7-96	115	50/60	20.3/22.3	5.7/6.4	29.6/33.5	2,500/3,200	140/120	13/11	B,S	③/④
FA8025B22T5-96	* 230	50/60	18.3/20.3	5.2/5.9	28.6/32.5	2,400/3,000	60/50	11/9	B,S	①/②
FA8025B22T7-96	* 230	50/60	20.3/22.3	5.7/6.4	29.6/33.5	2,500/3,200	65/55	12/10	B,S	③/④

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".
- If model depicts "*", UL approvals can be implemented upon request.

Specifications are subject to change without notice

