

# AC AXIAL FAN 120x120x38mm



**Housing:** Die-Cast Aluminum, Painted Black  
**Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 100MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 1500VAC for one minutue  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~85°C(Humidity 35%-85%RH)  
**Motor Protection:** Impedance Protected  
**Weight:** 520 g      **Packing:** 40PCS/CTN



Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1238B11T3-92	115	50/60	66.0/79.2	2.5/4.7	34.5/39.4	1,900/2,500	120/100	11/9	B,S	①/②
FA1238B11T5-92	115	50/60	81.2/91.4	4.7/6.2	38.4/42.4	2,500/2,800	170/130	14/10	B,S	③/④
FA1238B11T7-92	115	50/60	85.3/101.5	7.2/8.7	44.3/50.2	2,600/3,000	280/210	25/19	B,S	⑤/⑥
FA1238B22T3-92	230	50/60	66.0/79.2	2.5/4.7	34.5/39.4	1,900/2,500	60/50	12/10	B,S	①/②
FA1238B22T5-92	230	50/60	81.2/91.4	4.7/6.2	38.4/42.4	2,500/2,800	90/70	16/11	B,S	③/④
FA1238B22T7-92	230	50/60	85.3/101.5	7.2/8.7	44.3/50.2	2,600/3,000	130/90	21/15	B,S	⑤/⑥

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

