

AC AXIAL FAN
160x160x62mm
(Reverse Blow)



Housing: Die-Cast Aluminum, Painted Black
Blade: Injection Molded of Flame Retardant Polycarbonate, Black
Insulation Resistance: 100M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minutue
Operation Temperature: -20°C-70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C-85°C(Humidity 35%-85%RH)
Motor Protection: Thermally Protected
Weight: 1400 g **Packing:** 12PCS/CTN

Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1662B11T7C-51	115	50/60	261.0/307.0	14.7/19.6	60.0/64.0	2,900/3,400	450/500	51/58	B	①/②
FA1662B22T7C-51	230	50/60	261.0/305.0	14.7/19.6	60.0/64.0	2,900/3,400	230/250	51/57	B	①/②

• For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

AC Axial Fans

