

# AC AXIAL FAN 172x150x51 mm



**Housing:** Die-Cast Aluminum, Painted Black  
**Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 100MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 1500VAC for one minute  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~85°C(Humidity 35%-85%RH)  
**Motor Protection:** Impedance Protected  
**Weight:** 920 g      **Packing:** 16PCS/CTN



Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1751B11T5-96	115	50/60	141.1/176.6	10.3/12.4	42.4/47.3	2,350/2,550	400/380	28/27	B,S	①/②
FA1751B11T7-96	115	50/60	198.9/211.1	12.6/13.4	47.3/54.2	2,500/2,700	500/440	39/36	B,S	③/④
FA1751B22T5-96	230	50/60	141.1/176.6	10.3/12.4	42.4/47.3	2,350/2,550	180/170	25/24	B,S	①/②
FA1751B22T7-96	230	50/60	198.9/211.1	12.6/13.4	47.3/54.2	2,500/2,700	240/220	37/35	B,S	③/④

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

