

# AC AXIAL FAN 172x150x51mm



**Housing:** Die-Cast Aluminum, Painted Black  
**Blade:** Thermoplastic PBT, UL 94V-0  
**Insulation Resistance:** 100MΩ, 500VDC/min between bare wire and frame  
**Dielectric Strength:** 1500VAC for one minute  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~85°C(Humidity 35%-85%RH)  
**Motor Protection:** Impedance Protected  
**Weight:** 920 g      **Packing:** 16PCS/CTN



Model Number	Voltage (VAC)	Frequency (Hz)	AirFlow (CFM)	Stat.Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FA1751B11T7-97	115	50/60	211.1/198.9	13.7/12.1	52.2/60.1	2,500/2,800	660/580	51/47	B,S	①/②
FA1751B22T7-97	230	50/60	211.1/198.9	13.7/12.1	52.2/60.1	2,600/2,000	250/230	38/36	B,S	①/②

- For "Sleeve" bearing version, change the "B" in the model number to "S".
- For "Wire Lead" version, change the "T" in the model number to "W".

Specifications are subject to change without notice

