

AC AXIAL FAN 225*225*80mm



Housing: Aluminum Housing
Blade: Steel Impeller
Insulation Resistance: 100MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 1500VAC for one minute
Operation Temperature: -20°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~80°C(Humidity 35%-85%RH)
Motor Protection: Thermally Protected
Weight: 2750 g **Packing:** 6PCS/CTN



| Model Number | Voltage (VAC) | Frequency (Hz) | AirFlow (CFM) | Stat.Pres. (mm-H ₂ O) | Noise (dBA) | Speed (RPM) | Current (mA) | Power (W) | Available Bearing | Curves |
|-----------------|---------------|----------------|---------------|----------------------------------|-------------|-------------|--------------|-----------|-------------------|--------|
| FA2280B11T7C-55 | 115 | 50/60 | 558.7/680.1 | 13.7/20.8 | 67.0/69.9 | 2,750/3,150 | 730/720 | 59/70 | B | ①/② |
| FA2280B22T7C-55 | 230 | 50/60 | 558.7/680.1 | 13.7/20.8 | 67.0/69.9 | 2,750/3,150 | 320/320 | 58/70 | B | ①/② |

AC Axial Fans

