

DC BLOWER 57x57x12mm



Housing/Blade: Thermoplastic PBT, UL 94V-0
 Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 15%-90%RH)
 Storage Temperature: -10°C~70°C(Humidity 15%-90%RH)
 Lead Wire: UL Type #28 AWG
 Weight: 20 g Packing: 300PCS/CTN



| Model Number | Voltage (VDC) | Op.Voltage (VDC) | AirFlow (CFM) | StaticPres. (mm-H ₂ O) | Noise (dBA) | Speed (RPM) | Current (mA) | Power (W) | Available Bearing | Curves |
|-------------------|---------------|------------------|---------------|-----------------------------------|-------------|-------------|--------------|-----------|-------------------|--------|
| FBD5712B05W3-75 ★ | 5 | 4.5~5.5 | 2.00 | 3.00 | 10.60 | 2,500 | 80 | 0.40 | B | ① |
| FBD5712B05W5-75 ★ | 5 | 4.0~5.5 | 2.80 | 6.00 | 23.50 | 3,500 | 150 | 0.75 | B | ② |
| FBD5712B05W7-75 ★ | 5 | 4.0~5.5 | 3.70 | 11.00 | 28.20 | 4,500 | 250 | 1.25 | B | ③ |
| FBD5712B12W3-75 ★ | 12 | 7.0~13.8 | 2.80 | 6.00 | 23.50 | 3,500 | 80 | 0.96 | B | ② |
| FBD5712B12W5-75 ★ | 12 | 7.0~13.8 | 3.70 | 11.00 | 28.20 | 4,500 | 120 | 1.44 | B | ③ |
| FBD5712B12W7-75 ★ | 12 | 7.0~13.8 | 4.60 | 17.80 | 35.00 | 5,500 | 220 | 2.64 | B | ④ |
| FBD5712B12W9-75 ★ | 12 | 7.0~13.8 | 5.40 | 25.00 | 39.00 | 6,500 | 350 | 4.20 | B | ⑤ |

• If model depicts "★", auto restart protection function built in.

Specifications are subject to change without notice

