

DC AXIAL FAN 40x40x10mm



Housing/Blade: Thermalplastic PBT, UL 94V-0
Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -10°C~70°C(Humidity 35%~85%RH)
Storage Temperature: -40°C~80°C(Humidity 35%~85%RH)
Lead Wire: UL Type #26 AWG
Weight: 16 g **Packing:** 400PCS/CTN



Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD4010B05W3-61B ★▲	5	3.5~5.75	5.70	1.70	24.60	4,500	130	0.65	B,S	①
FD4010B05W5-61B ★▲	5	3.5~5.75	7.00	2.60	27.60	5,500	160	0.80	B,S	②
FD4010B05W7-61B ★▲	5	3.5~5.75	8.70	3.90	31.50	6,500	200	1.00	B,S	③
FD4010B12W3-61B ★▲	12	7.0~13.8	5.70	1.70	24.60	4,500	60	0.72	B,S	①
FD4010B12W5-61B ★▲	12	6.0~13.8	7.00	2.60	27.60	5,500	70	0.84	B,S	②
FD4010B12W7-61B ★▲	12	6.0~13.8	8.70	3.90	31.50	6,500	90	1.08	B,S	③
FD4010B24W3-61B ★▲	24	16.0~27.6	5.70	1.70	24.60	4,500	50	1.20	B,S	①
FD4010B24W5-61B ★▲	24	12.0~27.6	7.00	2.60	27.60	5,500	60	1.44	B,S	②
FD4010B24W7-61B ★▲	24	12.0~27.6	8.70	3.90	31.50	6,500	90	2.16	B,S	③

- For "Sleeve" bearing version, change the "B" in the model number to "S" respectively.
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

