


# DC AXIAL FAN 30x30x06mm



Housing/Blade: Thermoplastic LCP, UL 94V-0  
 Insulation Resistance: 10M $\Omega$ , 500VDC/min between bare wire and frame  
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame  
 Operation Temperature: -10°C~70°C(Humidity 15%-65%RH)  
 Storage Temperature: -20°C~85°C(Humidity 15%-65%RH)  
 Lead Wire: UL Type #32 AWG  
 Weight: 3.6 g      Packing: 1200PCS/CTN

Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD3006S05W3-88	★▲ 5	4.0~5.5	0.90	0.50	17.90	4,000	150	0.75	S	①
FD3006S05W5-88	★▲ 5	3.0~5.5	2.00	1.00	19.80	6,000	200	1.00	S	②
FD3006S05W7-88	★▲ 5	2.5~5.5	2.90	1.50	24.20	8,000	300	1.50	S	③
FD3006S05W9-88	★▲ 5	2.3~5.5	3.70	2.30	28.60	10,000	400	2.00	S	⑤
FD3006S12W3-88	★▲ 12	6.0~13.8	2.90	1.50	24.20	8,000	120	1.44	S	③
FD3006S12W5-88	★▲ 12	5.0~13.8	3.30	1.90	26.40	9,000	160	1.92	S	④
FD3006S12W7-88	★▲ 12	4.0~13.8	3.70	2.30	28.60	10,000	200	2.40	S	⑤
FD3006S12W9-88	★▲ 12	4.0~13.8	4.10	2.60	35.30	12,000	240	2.88	S	⑥

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

