

DC AXIAL FAN 40x40x28mm



Housing/Blade: Thermalplastic PBT, UL 94V-0
Insulation Resistance: 10MΩ, 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~80°C(Humidity 35%-85%RH)
Lead Wire: UL Type #26 AWG
Weight: 53 g **Packing:** 400PCS/CTN



Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD4028B12W3-63 ★▲	12	6.0~13.8	9.20	10.40	36.40	8,000	150	1.80	B	①
FD4028B12W5-63 ★▲	12	6.0~13.8	11.60	15.40	40.40	10,000	250	3.00	B	②
FD4028B12W7-63 ★▲	12	6.0~13.8	14.90	24.40	45.30	13,000	380	4.56	B	③
FD4028B12W9-63 ★▲	12	6.0~13.8	20.40	42.80	53.20	17,500	650	7.80	B	④
FD4028B24W3-63 ★▲	24	12.0~27.6	9.20	10.40	36.40	8,000	100	2.40	B	①
FD4028B24W5-63 ★▲	24	12.0~27.6	11.60	15.40	40.40	10,000	150	3.60	B	②
FD4028B24W7-63 ★▲	24	12.0~27.6	14.90	24.40	45.30	13,000	300	7.20	B	③

- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

