

DC AXIAL FAN 60x60x20mm



Housing/Blade: Thermalplastic PBT, UL 94V-0
Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
Storage Temperature: -40°C~80°C(Humidity 35%-85%RH)
Lead Wire: UL Type #24 AWG
Weight: 50 g **Packing:** 200PCS/CTN



Model Number		Voltage (VDC)	Op.Voltage (VDC)	AirFlow (CFM)	StaticPres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6020B12W3-61	★▲	12	6.0~13.8	15.90	2.40	25.60	3,000	80	0.96	B,S	①
FD6020B12W5-61	★▲	12	6.0~13.8	18.80	3.30	28.60	3,500	120	1.44	B,S	②
FD6020B12W7-61	★▲	12	6.0~13.8	22.60	4.80	34.50	4,200	160	1.92	B,S	③
FD6020B24W3-61	★▲※	24	12.0~27.6	15.90	2.40	25.60	3,000	80	1.92	B,S	①
FD6020B24W5-61	★▲※	24	12.0~27.6	18.80	3.30	28.60	3,500	100	2.40	B,S	②
FD6020B24W7-61	★▲※	24	12.0~27.6	22.60	4.80	34.50	4,200	130	3.12	B,S	③

- For "Sleeve" bearing version, change the "B" in the model number to "S" respectively.
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.
- If model depicts "※", UL and TUV approvals can be implemented upon request.

Specifications are subject to change without notice

