

DC AXIAL FAN 60x60x25mm



Housing/Blade: Thermalplastic PBT, UL 94V-0
 Insulation Resistance: 10M Ω , 500VDC/min between bare wire and frame
 Dielectric Strength: 5mA max. 500VAC/min between bare wire and frame
 Operation Temperature: -10°C~70°C(Humidity 35%-85%RH)
 Storage Temperature: -40°C~80°C(Humidity 35%-85%RH)
 Lead Wire: UL Type #24 AWG
 Weight: 62 g Packing: 200PCS/CTN



Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H ₂ O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD6025B12W3-61A ★▲	12	6.0~13.8	12.70	1.80	21.70	2,500	70	0.84	B,S	①
FD6025B12W5-61A ★▲	12	6.0~13.8	15.30	2.60	23.60	3,000	100	1.20	B,S	②
FD6025B12W7-61A ★▲	12	6.0~13.8	20.60	4.60	28.60	4,000	140	1.68	B,S	③
FD6025B24W3-61A ★▲	24	12.0~27.6	12.70	1.80	21.70	2,500	90	2.16	B,S	①
FD6025B24W5-61A ★▲	24	12.0~27.6	15.30	2.60	23.60	3,000	100	2.40	B,S	②
FD6025B24W7-61A ★▲	24	12.0~27.6	20.60	4.60	28.60	4,000	140	3.36	B,S	③
FD6025B48W3-61A ★▲	48	24.0~55.2	26.00	7.10	36.40	5,000	100	4.80	B,S	④
FD6025B48W5-61A ★▲	48	24.0~55.2	31.40	9.70	39.40	6,000	120	5.76	B,S	⑤
FD6025B48W7-61A ★▲	48	24.0~55.2	39.40	14.70	46.30	7,500	180	8.64	B,S	⑥
FD6025B60W3-61A ★▲※	60	36.0~72.0	26.00	7.10	36.40	5,000	200	12.00	B	④

- For "Sleeve" bearing version, change the "B" in the model number to "S" respectively.
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.
- If model depicts "※", TUV approvals can be implemented upon request.

Specifications are subject to change without notice

