

# DC AXIAL FAN 92x92x25mm



**Housing/Blade:** Thermalplastic PBT, UL 94V-0  
**Insulation Resistance:** 10M $\Omega$ , 500VDC/min between bare wire and frame  
**Dielectric Strength:** 5mA max. 500VAC/min between bare wire and frame  
**Operation Temperature:** -10°C~70°C(Humidity 35%-85%RH)  
**Storage Temperature:** -40°C~80°C(Humidity 35%-85%RH)  
**Lead Wire:** UL Type #24 AWG  
**Weight:** 85 g      **Packing:** 100PCS/CTN



Model Number	Voltage (VDC)	Op.Voltage (VDC)	Air Flow (CFM)	Static Pres. (mm-H <sub>2</sub> O)	Noise (dBA)	Speed (RPM)	Current (mA)	Power (W)	Available Bearing	Curves
FD9225B12W3-61	★▲ 12	6.0~13.8	37.70	2.30	28.60	2,000	160	1.92	B,S	①
FD9225B12W5-61	★▲ 12	6.0~13.8	47.70	3.20	33.50	2,500	190	2.28	B,S	②
FD9225B12W7-61	★▲ 12	6.0~13.8	53.10	4.10	36.40	2,800	230	2.76	B,S	③
FD9225B24W3-61	★▲ 24	12.0~27.6	37.70	2.30	28.60	2,000	150	3.60	B,S	①
FD9225B24W5-61	★▲ 24	12.0~27.6	47.70	3.20	33.50	2,500	180	4.32	B,S	②
FD9225B24W7-61	★▲ 24	12.0~27.6	53.10	4.10	36.40	2,800	220	5.28	B,S	③

- For "Sleeve" bearing version, change the "B" in the model number to "S" respectively.
- If model depicts "★", auto restart protection function built in.
- If model depicts "▲", polarity protection function built in.

Specifications are subject to change without notice

